

Plug Type Fixed Optical Attenuator (FOA)

Features:
Low Insertion Loss High Return Loss
Application:
Fiber Network

Specifications

Parameter	Plug Type
Type	FC/UPC, FC/APC, SC/UPC, SC/APC, LC/PC, LC/APC, MU/PC, ST/PC, E2000/UPC, E2000/APC
Wavelength (nm)	SM: 1310/1550 MM: 850
Fiber Type	SMF-28e or Multimode 50um or 62.5/125
Attenuation range (dB)	0-30 dB
Return Loss (dB)	≥50 (UPC), ≥60 (APC)-SM
Attenuation precision (dB)	1-5dB ≤ +/-0.5 5-30dB ≤ +/-10%
Operating temperature (°C)	-40~85
Storage temperature (°C)	-40 ~ 85



Ordering Information

FOA	Type	0000000	Attenuation	Mode	Connector
	P=Plug Type		01=1 03=3 05=5 10=10dB 15=15dB 20=20dB 25=25dB 30=30dB XX: Specify	1=SMF-28e 2=MM 50/125 3=MM 62.5/125	0=None 1=FC/UPC 2=FC/APC 3=SC/APC 4=SC/UPC 5=MU 6=LC/UPC 7=LC/APC S=Specify